



optical transport network infrastructure.



# **KEY BENEFITS**

- Highly reliable, non-blocking switching capacity
- Streamline fixed and mobile networks into a converged network
- Integrate open NOS applications for highly reliable and flexible networks
- Futureproof to meet evolving requirements of 5G with ultra-low latency, high precision frequency and phase timing synchronization support
- Quick and easy installation onto standard 19" server racks
- User friendly maintenance design with redundant and hot swappable power and fan modules

# **KEY FEATURES**

400G ZR/ZR+ transceivers from multiple vendors to enable long distance optical transmissions while simplifying the

- High-density 40x100G interfaces for large-volume traffic aggregation
- 8x 400G interfaces with OpenZR+ support
- 7.2Tbps switching capacity with a high performance 12-Core, 1.8 GHz processor
- 8GB Deep buffer
- Class C timing accuracy support
- Fully supports SyncE and IEEE 1588v2 timing synchronization profiles
- Integrated Stratum 3E OCXO with optional hold over performances
- Support full Segment Routing over IPv6 (SRv6)
- MACsec supports on all ports
- TCAM option available to meet diverse deployment requirements

# **SPECIFICATIONS**

# PHYSICAL

8 x 40/100/200/400G QSFP-DD ports with 400G ZR/ZR+ support

40 x 40/100G QSFP28 ports

4 x 10/25G SFP28/SFPDD ports (In-band port share with 100GE Port 0)

• 4 x 10G SFP+ management ports

1 x RJ45 & Micro USB serial console port

• 1 x 100/1000M RJ45 management port

1 x USB 3.0 Type-A port

Processor Intel Icelake-D 12-Core @ 1.8GHz Memory 64G DDR4 Storage 2 x 256G SSD ASIC Broadcom Qumran2c+ BCM88840 AST2620 BMC1 x GNSS input SMA Interfaces 1 x 10MHz input/output SMB **Timing** 1 x 1PPS input/output SMB 1 x ToD input/output RJ45 1 x BITS input/output RJ48

Stratum 3E OCXO **Timing** 

Support\*

ITU-T Synchronous Ethernet (SyncE) IEEE 1588v2 - Default, G.8265.1 G.8275.1, G.8275.2, SMPTE ST 2059-2\*\*, T-GM, T-BC/OC, T-TC

2 RU, 436 x 762 x 87.7 mm Chassis or 17.17" x 30" x 3.45'

(WxDxH) Weight: 22.64kg or 49.91lb (without FRU) Hot-swappable, 1+1 redundant PSU Redundancy Hot-swappable, 3+1 redundant Fans

\*NOS integration is necessary to activate the specific feature. \*\*Additional license is required

**ENVIRONMENTAL** 

Power Specs.	AC input: 200 to 240V, 12.5A DC input: -40 to -72V, 60A Typical Power: 548 W (no transceiver)
Max. Operating Specs.	Operating temperature: 0°C to 45°C (32°F to 113°F) Operating humidity: 5% to 85% (RH), non-condensing
Max. Non-Operating	Storage temperature: –40°C to 70°C (–40°F to 158°F)

Storage humidity: 5% to 93% (RH), non-condensing

## **PERFORMANCE**

Max. Non-Operating

Specs.

Switching Capacity	7.2Tbps
Deep Buffer	8GB

# REGULATORY COMPLIANCE

Specifications are subject to change without notice Contact our sales team for current configuration options.

# S9610-48DX

S9610-48DX Front and Rear Views





# **ACCESSORIES**

#### Compatible Transceivers Types

400G QSFP-DD SR, 400G QSFP-DD LR, 400G QSFP-DD ER, 400G QSFP-DD ZR, 400G QSFP-DD OpenZR+, 100G QSFP28 SR, 100G QSFP28 LR, 100G QSFP28 ER, 100G QSFP28 ZR, 100G QSFP28 OpenZR+, 25G SFP28 SR, 25G SFP28 LR, 10G SFP+ SR, 10G SFP+ LR

## Compatible Timing Cable Types

50 ohms SMA coaxial cable with 1/4-36UNS-2B connector for GNSS 50 ohms SMB coaxial cable with 10-32UNF-2A connector for 1PPS and 10MHz Shield cable with RJ45 for ToD Shield cable with RJ48 for BITS

# **Available to Order**

## Power Supply Types

PSU-202-DESR, 2000W DC, exhaust air flow PSU-202-AESR, 2000W AC, exhaust air flow

## **FAN Types**

FAN-808012-HCE, exhaust air flow



Solutions

**Networking** 

Telecom